




1-866-443-6623 www.holdupdisplays.com

HDSW2-3X4 6-Piece Gun Wall

\*Note: The connector plates are *ONLY* needed if joining rail end-to-end to mount two walls side by side.





Insert connector plate into back of slatwall. Press rails together. Grasping the top rail, tap rails on a rug or a non-marring surface to close gap.



Rails will be nested back-to-back for safe shipping. Be sure to separate before assembling. (It may be necessary to use a screwdriver to separate rails)

2



Choose a location and height for your rack taking into consideration clearance required to add and remove firearms from racks. Begin installation with the lowest row of rails.

3



Hold rail against wall with the stacking tab down as shown above. Check level and draw a line along the top of the rail.



Extend lines vertically to the full height of the 36" display and recheck stud alignment.



Using your preferred method, locate and mark every stud along the line. NOTE: Studs must be within 7" of the end of the rail. When joining rails end to end if a stud aligns with joint of the two rails, move display 1" left or right.

6



Insert mounting screw into screw guide.




The mounting screws included are self-drilling. The screw itself will drill the hole it requires.



Place screw guide into channel at stud location. Firmly press both guide and drill against rail and drive screw through channel into stud.







Mark and attach with screws each additional row to complete wall.

11



Insert screw cover strip from end of rail if accessible, otherwise press into slot with pen or marker.



Remove paper backing from white adhesive square Place face down on rails as shown. Remove paperbacking from second side and align end cap for desired finish.

12



Press end cap firmly against rails for maximum bond strength. (Adhesive bonds instantly so you have one chance)

