



1-866-443-6623 www.holdupdisplays.com

HDSW24
Slatwall Rail

*Note: The connector plates are *ONLY* needed if joining rail end-to-end to mount two walls side by side.



Insert connector plate into back of slatwall. Press rails together. Grasping the top rail, tap rails on a rug or a non-marring surface to close gap.



Rails will be nested back-to-back for safe shipping. Be sure to separate before assembling. (It may be necessary to use a screwdriver to separate rails)

2



Choose a location and height for your rack taking into consideration clearance required to add and remove instruments from racks.

Begin installation with the lowest row of rails.





Hold rail against wall with the stacking tab down as shown above. Check level and draw a line along the top of the rail.



Using your preferred method, locate and mark every stud along the line.

NOTE: Studs must be within 7" of the end of the rail. When joining rails end to end if a stud aligns with joint of the two rails, move display 1" left or right.



If stacking multiple rails: Extend lines vertically to the full height of the display and recheck stud alignment. Transfer stud marks to channel.



6

Insert mounting screw into screw guide.



The mounting screws included are self-drilling. The screw itself will drill the hole it requires.



Place screw guide into channel at stud location. Firmly press both guide and drill against rail and drive screw through channel into stud.

Check level and drive screws at each stud location in both the top and bottom channels.




Mark and attach with screws each additional row to complete wall.





Insert screw cover strip from end





Remove paper backing from white adhesive square. Place face down on rail as shown. Remove paper backing from second side and align end cap for desired finish



Press end cap firmly against rail for maximum bond strength. (Adhesive bonds instantly so you have one chance)

